

OXYGEN ACETYLENE WELDING HOSE

Description

Inner Tube :

black synthetic rubber - delivering gas for long-term use.

Reinforcement Layer:

high strength synthetic cord - Meet work pressure requirements.

Cover:

synthetic rubber in blue, red and green - working at tough condition and complex environment.

Temperature :

-32°C (-90°F) to 80°C (+176°F)



OXYGEN HOSE 300PSI / ACETYLENE HOSE 300PSI

I.D		O.D	W.P		B.P		L	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/16"	4.8	12	20	300	60	900	100	330
1/4"	6.4	13	20	300	60	900	100	330
5/16"	7.9	15	20	300	60	900	100	330
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	21	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330

TWIN WELDING HOSE

I.D		O.D	W.P		B.P		L	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/16"	4.8+4.8	12+12	20	300	60	900	100	330
1/4"	6.4+6.4	13+13	20	300	60	900	100	330
5/16"	7.9+7.9	15+15	20	300	60	900	100	330
5/16"+3/8"	7.9+9.5	15+17	20	300	60	900	100	330
3/8"	9.5+9.5	17+17	20	300	60	900	100	330

Application Fields:

Mainly used in transport manufacturing, ship building, aircraft manufacturer and metal products, etc.

Product features:

Aging resistance
Abrasion resistance
Weather and ozone resistant
Good flexibility without distortion