

NITRILE FUEL DISCHARGE HOSE 300 PSI

Description

Inner Tube :
Black NR & SBR rubber - delivering oil and liquids for long-term use.

Reinforcement Layer:
High strength synthetic fiber - Meet work pressure requirements.

Cover :
Synthetic rubber with wrapped surface - it can work at tough condition and complex environment.

Temperature:
-32°C to +82°C (-90°F to +180°F)



I.D		O.D	W.P		B.P		L	
inch	mm	mm	bar	psi	bar	psi	m	ft
1/2"	12.7	22	20	300	60	900	61	200
5/8"	15.9	26	20	300	60	900	61	200
3/4"	19.1	31	20	300	60	900	61	200
7/8	22.2	32	20	300	60	900	61	200
1	25.4	36	20	300	60	900	61	200
1-1/4"	31.8	45	20	300	60	900	61	200
1-1/2"	38.1	51	20	300	60	900	61	200
2	50.8	65	20	300	60	900	61	200
1-1/2"	63.5	79	20	300	60	900	61	200
3	76.2	91	20	300	60	900	61	200
3-1/2"	88.9	107	20	300	60	900	61	200
4	101.6	120	20	300	60	900	61	200
5	127	148	20	300	60	900	30.5	100
6	152.4	173	20	300	60	900	30.5	100
8	203.2	228	20	300	60	900	30.5	100

Application Fields:

Mainly used for conveying oil and other liquids, It is widely used in construction, oil field mining, engineering construction, road construction. Transfer and discharge petroleum-based liquids, diesel, gasoline, lubricant, fuel.

Product features:

Aging resistance
Abrasion resistance
Flexible and non-distortion
Weather and ozone resistant