

NITRILE FUEL HOSE 300 PSI



Description

Inner Tube :

Black NR & SBR rubber - delivering oil and liquids for long-term use.

Reinforcement Layer:

High strength synthetic yarn - Meet work pressure requirements.

Cover :

Synthetic rubber - it can work at tough condition and complex environment.

Temperature:

-32°C to +82°C (-90°F to +180°F)

I.D		O.D	W.P		B.P			M ³	kg
inch	mm	mm	bar	psi	bar	psi	m	m ³ /roll	kg/m
3/16"	5	12	20	300	60	900	100	410×410×100	0.15
1/4"	6	13	20	300	60	900	100	440×440×110	0.17
5/16"	8	15	20	300	60	900	100	490×490×120	0.22
3/8"	10	17	20	300	60	900	100	500×500×125	0.25
1/2"	13	22	20	300	60	900	100	480×480×135	0.46
5/8"	16	25	20	300	60	900	50	480×480×150	0.52
3/4"	19	29	20	300	60	900	50	520×520×185	0.64
1"	25	36	20	300	60	900	50	590×590×210	0.85
1-1/4"	32	43	10	150	30	450	50	0.17	1.2
1-1/2"	38	50	10	150	30	450	50	0.19	1.39
2"	51	65	10	150	30	450	50	0.41	1.8

Application Fields:

Mainly used for conveying oil and other liquids, It is widely used in construction, oil field mining, engineering construction, road construction. Transfer and discharge petroleum-based liquids, diesel, gasoline, lubricant, fuel.

Product features:

Aging resistance
Abrasion resistance
Flexible and non-distortion
Weather and ozone resistant