

SAND BLAST HOSE



Description

Inner tube:

black smooth, abrasion resistant synthetic rubber

Reinforcement: multiple layer of high tensile fiber braids

Cover:

black smooth or wrapped abrasion resistant synthetic rubber

Temperature:

-40°C to +70°C (-40 °F to +158 °F)

I.D		O.D	W.P		B.P		L	
mm	inch	mm	bar	psi	bar	psi	m	ft
1/2"	12.7	25	174	12	522	36	40	131
5/8"	15.9	30	174	12	522	36	40	131
3/4"	19.1	34	174	12	522	36	40	131
1"	25.4	38	174	12	522	36	40	131
1"	25.4	47	174	12	522	36	40	131
1-1/4"	31.8	48	174	12	522	36	40	131
1-1/2"	38.1	54	174	12	522	36	40	131
2"	50.8	69	174	12	522	36	40	131
2-1/2"	64	84	174	12	522	36	40	131
3"	76.2	96	174	12	522	36	40	131
4"	102	124	174	12	522	36	40	131
5"	127	149	174	12	522	36	40	131
6"	152	177	174	12	522	36	40	131

Application Fields:

Mainly used for Industrial cleaning, cutting, polishing, casting, rust cleaning for ship and machine.

Product features:

Aging resistance
Abrasion resistance
Weather and ozone resistant