

WATER DISCHARGE HOSE 300 PSI

Description

Inner Tube :

Black NR & SBR compound rubber for long-term use.

Reinforcement Layer:

High strength synthetic fibre

Cover :

SBR compound rubber with smooth or wrapped surface

Temperature :

-40°C (-104°F) to 80°C (+176°F)



I.D		O.D	W.P		B.P		L	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/16"	4.8	12	20	300	60	900	100	330
1/4"	6.4	13	20	300	60	900	100	330
5/16"	7.9	15	20	300	60	900	100	330
3/8"	9.5	16	20	300	60	900	100	330
1/2"	12.7	22	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330
1-1/4"	31.8	44	17	250	51	750	60	200
1-1/2"	38.1	51	17	250	51	750	60	200
2"	50.8	65	17	250	51	750	60	200
2-1/2"	63.5	78	17	250	51	750	60	200
3"	76.2	91	17	250	51	750	60	200
3-1/2"	88.9	108	17	250	51	750	60	200
4"	101.6	120	17	250	51	750	60	200
5"	127	148	17	250	51	750	30	100
6"	152.4	173	17	250	51	750	30	100
8"	203.2	228	17	250	51	750	30	100
10"	254	280	17	250	51	750	12	40
12"	304.8	330	17	250	51	750	12	40

Application Fields:

Mainly used for conveying water and other liquids, It is widely used in construction, oil field mining, engineering construction, road construction.

Product features:

Aging resistance
Abrasion resistance
Weather and ozone resistant